

CAVI MULTIPLI IN GOMMA DI SILICONE

MULTI-CORE CONDUCTOR SILICONE RUBBER INSULATED CABLES

GS MULTIPLO
N2GMH2G



| CODICE INTERNO ISOLET | N° CONDUTTORI x SEZIONE | DIAMETRO ESTERNO |
|-----------------------|-------------------------|------------------|
| ISOLET INTERNAL CODE | N° CONDUCTORS x SECTION | OUTER DIAMETER |
| | mm ² | mm |
| 0872A | 2 x 0,50 | 5,40 |
| 0872E | 2 x 0,75 | 6,40 |
| 0872H | 2 x 1,00 | 6,60 |
| 0872K | 2 x 1,50 | 7,60 |
| 0872L | 2 x 2,50 | 9,20 |
| 0872P | 3 x 0,50 | 5,90 |
| 0872R | 3 x 0,75 | 6,80 |
| 0872S | 3 x 1,00 | 7,40 |
| 0872T | 3 x 1,50 | 8,00 |
| 0872V | 3 x 2,50 | 9,70 |
| 0872W | 3 x 4,00 | 11,4 |
| 0872X | 3 x 6,00 | 14,2 |

| CODICE INTERNO ISOLET | N° CONDUTTORI x SEZIONE | DIAMETRO ESTERNO |
|-----------------------|-------------------------|------------------|
| ISOLET INTERNAL CODE | N° CONDUCTORS x SECTION | OUTER DIAMETER |
| | mm ² | mm |
| 0873A | 4 x 0,50 | 6,40 |
| 0873E | 4 x 0,75 | 7,80 |
| 0873H | 4 x 1,00 | 8,00 |
| 0873K | 7 x 4,00 | 16,2 |
| 0873L | 4 x 1,50 | 8,80 |
| 0873P | 4 x 2,50 | 10,6 |
| 0873Q | 5 x 1,00 | 9,80 |
| 0873QQ | 5 x 0,75 | 9,40 |
| 0873R | 7 x 6,00 | 19,2 |
| 0873S | 5 x 1,50 | 11,5 |
| 0873T | 4 x 4,00 | 13,1 |
| 0873U | 7 x 1,00 | 9,50 |
| 0873V | 7 x 2,50 | 12,6 |
| 0873W | 4 x 6,00 | 16,2 |
| 0873X | 5 x 2,50 | 14,0 |
| 0873Y | 4 x 10,0 | 20,0 |
| 0873Z | 7 x 1,50 | 10,4 |
| 0873ZZ | 8 x 1,50 | 11,8 |

Proprietà

- Isolamento in gomma di silicone
- Conduttore in Rame Stagnato
- Formazione del conduttore flessibile
- Classe di isolamento termico H
- Proprietà termiche da -60°C a +180°C - Punta fino a 250°C
- Resistente a: acqua, ozono, alcali, ammoniaca, fenoli, funghi
- Colori: bianco, nero, rosso, blu, marrone, grigio, giallo/verde

Properties

- Silicone rubber insulation
- Tinned Copper conductor
- Flexible conductor formation
- Thermal insulation class H
- Thermal properties from -60°C to +180°C - Peaks up until 250°C
- Resistant to: water, ozone, alkali, ammonia, phenols, fungus
- Colours: white, black, red, blue, brown, gray, yellow/green

Informazioni

Per ogni eventuale altra informazione di natura tecnica, sicurezza, normativa, consultare il sito: www.encocavi.com

Information

For any additional information upon technical use, safety standards, regulations, refer to the website: www.encocavi.com

elexa cavi s.r.l.

Via alle Fabbriche 20 - 10072
Caselle Torinese - TO - ITALY
Tel. +390119975151
Fax +390119975157
info@elexa.it
www.elexa.it
P.IVA/VAT 10423220010
ISO 9001.2000 n. 13705/05/S

isolet
industriale srl

Via alle Fabbriche 20 - 10072
CASELLE T.se (TO) ITALY
Tel. +390119914186
Fax +390119975157
IVA/CF/VAT IT 10414550011
info@isolet.it
www.isolet.it