

DERAY-IAKT : TUBETTO TERMORESTRINGENTE IN POLIOLEFINA RETICOLATA CON RIVESTIMENTO ADESIVO



DERAY-IAKT : ADHESIVE LINED CROSSLINKED POLYOLEFIN HEAT-SHRINK SLEEVE

3:1			4:1		
CODICE INTERNO ISOLET	DIAMETRO	DIAMETRO RISTRETTO	CODICE INTERNO ISOLET	DIAMETRO	DIAMETRO RISTRETTO
ISOLET INTERNAL CODE	DIAMETER	SHRINKED DIAMETER	ISOLET INTERNAL CODE	DIAMETER	SHRINKED DIAMETER
	mm	mm		mm	mm
0061A	3,00	1,00	0061R	4,00	1,00
0061B	4,80	1,60	0061S	8,00	2,00
0061E	6,00	2,00	0061T	12,0	3,00
0061H	9,00	3,00	0061U	16,0	4,00
0061K	12,0	4,00	0061V	24,0	6,00
0061L	19,0	6,00	0061W	32,0	8,00
0061M	24,0	8,00	0061X	52,0	13,0
0061P	40,0	13,0			

Proprietà

- Temperatura di esercizio: -55°C ÷ +110°C
- Temperatura di retrazione: +110°C
- Rapporto retrazione: 3:1 - 4:1
- Sono disponibili altre tipologie con caratteristiche particolari
- Colore: nero
- Confezione: barre da 1,2 mt o bobine
- Fuori standard a richiesta: 60 mt (da 3,0 a 6,0 mm)
30 mt (da 9,0 a 12,0 mm)
18 mt (da 19,0 a 25,0 mm)

Informazioni

Per ogni eventuale altra informazione di natura tecnica, sicurezza, normativa, consultare il sito: www.elexacavi.com

Properties

- Working temperature: -55°C ÷ +110°C
- Shrinking temperature: +110°C
- Shrinking ratio: 3:1 - 4:1
- Other typologies with particular characteristics available
- Colour: black
- Packaging: 1,2 mt boards or reels
- Non-standard upon request: 60 mt (from 3,0 to 6,0 mm)
30 mt (from 9,0 to 12,0 mm)
18 mt (from 19,0 to 25,0 mm)

Information

For any additional information upon technical use, safety standards, regulations, refer to the website: www.elexacavi.com