

# TUBETTO TERMORETRAIBILE IN PVC

PVC HEAT-SHRINK SLEEVE



CODICE INTERNO ISOLET	DIAMETRO	DIAMETRO RISTRETTO	SPESSORE
ISOLET INTERNAL CODE	DIAMETER	SHRINKED DIAMETER	THICKNESS
	mm	mm	mm
0050A	1,60	0,80	0,35
0050E	2,40	1,20	0,43
0050H	3,20	1,60	0,43
0050L	4,80	2,40	0,43
0050P	6,40	3,20	0,56
0050T	9,50	4,70	0,56
0050W	12,7	6,30	0,56
0050X	16,0	8,00	0,56
0051B	19,0	9,50	0,68
0051G	25,4	12,7	0,76
0051H	32,0	16,0	0,80
0051P	38,1	19,0	0,80
0051TT	50,8	26,0	0,80
0051V	76,2	36,0	1,00
0051W	101,6	48,0	1,00

## Proprietà

- Restringimento: 50%
- Rigidità dielettrica kV: 70 kV/mm
- Costante dielettrica: 4.3
- Temperatura di esercizio: +105°C
- Resistenza alla trazione: 210 kg/cm<sup>2</sup>
- Allungamento: 200%
- Autoestingente
- Colore: nero (altri a richiesta)
- Spezzonabile a misura

## Informazioni

Per ogni eventuale altra informazione di natura tecnica, sicurezza, normativa, consultare il sito: [www.elexacavi.com](http://www.elexacavi.com)

## Properties

- Shrinking: 50%
- Dielectric strength kV: 70 kV/mm
- Dielectric constant: 4.3
- Working temperature: +105°C
- Break load: 130 kg/cm<sup>2</sup>
- Stretching: 200%
- Self-extinguishing
- Colour: black (others upon request)
- Fragmentation requests accepted

## Information

For any additional information upon technical use, safety standards, regulations, refer to the website: [www.elexacavi.com](http://www.elexacavi.com)



Via alle Fabbriche 20 - 10072  
Caselle Torinese - TO - ITALY  
Tel. +390119975157  
Fax +390119975157  
info@elexa.it  
www.elexa.it  
P.IVA/VAT 10423220010  
ISO 9001.2000 n. 13705/05/S



Via alle Fabbriche 20 - 10072  
CASELLE T.se (TO) ITALY  
Tel. +390119975157  
Fax +390119975157  
IVA/CF/VAT IT 10414550011  
info@isolet.it  
www.isolet.it